

# J2 Fabric-Wrapped Dual Density Acoustic Panel

## PRODUCT DATA AND SPECIFICATIONS

Made with a rigid fiberglass core, a 1/8" high-impact facing, and edge-hardened, these panels are wrapped with a variety of acoustic fabric colors and have tailored corners. They are ideal for spaces like conference rooms, auditoriums, meeting halls, or anywhere sound absorption is needed.

### Composition

Resin-bonded borosilicate glass fiber, chemically-hardened edges

### Thickness

7/8-inch, 1-inch, 2-inch, other custom thicknesses available

### Density

6-7 PCF core, 14-16 PCF 1/8" high-impact facing

### Dimensions

Standard Sizes: 2x2, 2x4, 4x4, 4x6, 4x8, custom sizes available up to 48x120

### Fire Rating

ASTM E84 and UL 723 and CAN/ULC S102-M88  
Meets NFPA 90A and 90B

### Acoustic NRC

0.75 at 7/8 in. thickness, 0.85 at 1 in. thickness, 0.95 at 2 in. thickness


### Application

Wall and ceiling panels

### Material Notes

Acoustical fabrics from Guilford of Maine, or customize with printed designs

### Edge Detail




### Mounting Options

Adhesive, finish Nails, Z-clip attachments, impaling clips


### Warranty


2-year warranty against workmanship and manufacturing defects


### Diagram:



 [www.j2systems.net](http://www.j2systems.net)

 [sales@j2systems.net](mailto:sales@j2systems.net)

 (801) 701-7979

 1750 S 500 W, Ste 300  
Salt Lake City, UT 84115