

J2 PET Acoustic Felt - 3mm

PRODUCT DATA AND SPECIFICATIONS



J2 PET Felt Fabric adds a pop of color and a soft texture to wall and ceiling surfaces. Available in full rolls, it can also be cut to specific sizes, shapes, or patterns.

- ✓ Eco-friendly
- ✓ 100% PET Felt
- ✓ Durable
- ✓ Hard-Wearing
- ✓ Tackable
- ✓ 45 Color Options

COMPOSITION: 100% PET (>75% recycled PET material)

THICKNESS: 3mm

DENSITY: 600g/sqm (approx 0.12 psf)

ROLL DIMENSIONS: 1m x 50m (39.5in x 164ft)

FIRE RATING: ASTM E84 – Class C

APPLICATION: Wall and ceiling

MATERIAL NOTES: Variation in thickness, fiber mix and color, as well as flecks and other slight surface blemishes are an inherent feature of this product and are unavoidable. Variation from batch to batch may occur.

CLEANING & CARE: Remove dust and dirt by dusting, vacuuming, or with a soft cloth or sponge and a solution of carpet or upholstery shampoo. Use a soft, damp cloth and blot dry. Spot cleaner can be used for lightly soiled areas.

MOUNTING OPTIONS: Felt fabric can be installed on wall and ceiling surfaces via fasteners, or contact adhesives. When installing with adhesives, the fabric can be mounted directly to the surface.

WARRANTY: 4-year warranty against workmanship and manufacturing defects.