## J2 PET Batten Panel

## PRODUCT DATA AND SPECIFICATIONS



J2 Batten Panels enhance the design of any space with an attractive linear look and strong acoustic performance. PET or Printed Wood Grain options are both available.

- Custom Patterns Optional
- ✓ Lightweight
- Varying Widths

- → 7 Wood Grain Print Options
- Enhances Acoustics
- ✓ 34 PET Color Options

STYLE: Wall or ceiling mounted panels, slat width and spacing can be varied and

COMPOSITION: 100% PET (>75% recycled PET material)

THICKNESS: 24mm, and other custom thicknesses available

PET DENSITY: 1900g/sqm-2400g/sqm (approx 12pcf)

**DIMENSIONS:** 47.5 in x 95.5 in, or custom within those dimensions,

Standard slat width is 2 in

FIRE RATING: ASTM E84 - Class B (Class A panels available on request)

ACOUSTIC NRC: 0.50 to 0.90 - varies by pattern and thickness

**APPLICATION:** Ceiling or wall mount

HARDWARE & INSTALLATION:

Panels may be applied directly to wall and ceiling surfaces using construction adhesive, z-clips, or finish nails. Optional hardware includes anodized or powder-coated aluminum J-Trim for panel perimeter, or H-Trim for joining panels.

**WARRANTY:** 4-year warranty against workmanship and manufacturing defects

## PRODUCT DIAGRAMS:



