

J2 PET Contrast Panel

PRODUCT DATA AND SPECIFICATIONS



J2 PET Contrast Panels combine stylish and creative pattern designs with a pop of contrasting color and enhanced acoustic performance. Mix and match to customize your look.

- ✓ Standard Patterns Available
- ✓ Custom Pattern Options
- ✓ Eco-friendly
- ✓ Durable
- ✓ Tackable
- ✓ 34 Color Options

STYLE: Wall mounted design panels, standard patterns or custom design available

COMPOSITION: 100% PET (>75% recycled PET material)

THICKNESS: 24mm total: 12mm background panel, 12mm design panel

DENSITY: 1900g/sqm-2400g/sqm (approx 12pcf)

DIMENSIONS: 47.5in x 95.5in, or custom within those dimensions

FIRE RATING: ASTM E84 – Class B (Class A panels available on request)

ACOUSTIC NRC: .50 to .70 - varies by pattern

APPLICATION: Wall Mounted

HARDWARE & INSTALLATION: Panels can be installed on wall surfaces via fasteners, or standard construction adhesives. When installing with adhesives, the panels can be mounted directly to the surface, or furring strips can be installed to create an air gap behind the panels.

WARRANTY: 4-year warranty against workmanship and manufacturing defects

PRODUCT DIAGRAM:

