J2 PET Felt Tiles

PRODUCT DATA AND SPECIFICATIONS



J2 PET Acoustic Felt Tiles provide excellent sound absorption without compromising on aesthetic function. Tiles can be cut in any shape or size to accommodate design specifications.

- ✓ Eco-friendly
- LightweightHard-WecTackable
- ✓ Durable

- ✓ Hard-Wearing
- ✓ 34 Color Options

COMPOSITION:	100% PET (>75% recycled PET material)
THICKNESS:	9mm, 12mm, other custom thicknesses available
DENSITY:	1900g/sqm-2400g/sqm (approx 12pcf)
DIMENSIONS:	See details on page 2. Custom sizes available
FIRE RATING:	ASTM E84 – Class B (Class A panels availabe on request, color options may vary) EN13501 - Class B
ACOUSTIC NRC:	0.3-0.9 Depending on thickness and airgap
APPLICATION:	Wall and ceiling
MATERIAL NOTES:	Variation in thickness, fiber mix and color, as well as flecks and other slight surface blemishes are an inherent feature of this product and are unavoidable. Variation from batch to batch may occur.
CLEANING & CARE:	Remove dust and dirt by dusting, vacuuming, or with a soft cloth or sponge and a solution of carpet or upholstery shampoo. Use a soft, damp cloth and blot dry. Spot cleaner can be used for lightly soiled areas.
MOUNTING OPTIONS:	Tiles can be installed on wall and ceiling surfaces via fasteners, or standard construction adhesives. When installing with adhesives, the tiles can be mounted directly to the surface, or furring strips can be installed to create an air gap behind the tiles.
WARRANTY:	4-year warranty against workmanship and manufacturing defects.

12MM PET ACOUSTIC FELT NRC COMPARISON:

Frequency/Hz	100	125	160	200	250	315	400	500	630	800	1000	1250	1600	2000	2500	3150	4000	NRC
No Cavity	0.04	0.03	0.04	0.05	0.06	0.10	0.11	0.22	0.30	0.43	0.55	0.65	0.73	0.82	0.92	0.98	1.03	0.40
50mm / 2in	0.16	0.16	0.19	0.29	0.38	0.48	0.61	0.75	0.83	0.97	0.97	0.93	0.96	0.91	0.86	0.83	0.89	0.75
150mm / 6in	0.26	0.37	0.41	0.62	0.68	0.82	0.89	0.98	0.90	0.92	0.81	0.75	0.82	0.87	0.87	0.90	0.90	0.85







J2 PET Felt Tiles

STYLE OPTIONS AND STANDARD SIZES

